



Weldon Materials, Inc.

READY MIX CONCRETE

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

| | |
|--|---|
| Product identifier | Ready Mix Concrete |
| Chemical Name | Mixture |
| CAS No. | Mixture |
| Trade Name(s) | Concrete |
| Relevant identified uses of the substance or mixture and uses advised against | |
| Identified Use(s) | Construction material |
| Uses Advised Against | None. |
| Details of the supplier of the safety data sheet | |
| Company Identification | Weldon Materials 141 Central Ave Westfield, NJ 07090 |
| Telephone | 908-233-4444 |
| Emergency telephone number | |
| Emergency Phone No. | Not classified as dangerous for supply/use. Please contact the supplier above during normal business hours. |

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) / GHS Classification Eye Dam. 1; Skin Corr. 1C; Skin Sens. 1B

Label elements

Hazard Symbol



DANGER

Signal Word(s)

Hazard Statement(s)

Causes severe skin burns and eye damage.
May cause an allergic skin reaction.

Precautionary Statement(s)

Wear protective gloves/protective clothing/eye protection/face protection.
Wash hands and exposed skin after use.

Other hazards

Mechanical disruption (e.g., milling, cutting, chipping) of cured concrete may release crystalline silica dust which: Causes damage to organs: Lungs (silicosis) and May cause cancer: Lungs. Avoid breathing dust. Wear suitable respiratory protective equipment if processing involves working in areas where dusts are likely to be evolved.

Additional Information

None



READY MIX CONCRETE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Composition/information on ingredients | % wt. | CAS No. |
|---|---------|-----------|
| Aggregate (crushed stone, sand, gravel, slag) | > 50 | Various |
| Portland Cement ^ | 10 - 30 | 8052-42-4 |
| Water | 10 - 20 | 7732-18-5 |

^Contains: <0.1% hexavalent chromium (CrVI) metals and salts.

Other Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below. Please see Section 8 of SDS for more details.

- Mechanical disruption (e.g., milling, cutting, chipping) of cured concrete may release crystalline silica dust.

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

| | |
|---|---|
| Inhalation | Not normally required. Move person to fresh air. Apply artificial respiration if necessary. If symptoms persist, obtain medical attention. |
| Skin Contact | Wash immediately with water. Table vinegar and additional water may help to neutralize and prevent skin burns. If irritation (redness, rash, blistering) develops, get medical attention. |
| Eye Contact | Flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention. |
| Ingestion | Not normally required. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell. |
| Most important symptoms and effects, both acute and delayed | May cause an allergic skin reaction. Contains: trace chromium metals and salts inherent in portland cement. |
| Indication of any immediate medical attention and special treatment needed | None known |

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Non-combustible. As appropriate for surrounding fire.
None anticipated.

Special hazards arising from the substance or mixture

None known

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions.



Weldon Materials, Inc.

READY MIX CONCRETE

SECTION 6: ACCIDENTAL RELEASE MEASURES

| | |
|--|------------------------|
| Personal precautions, protective equipment and emergency procedures | Not normally required. |
| Environmental precautions | Not normally required. |
| Methods and material for containment and cleaning up | Not normally required. |
| Reference to other sections | None |
| Additional Information | None. |

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling Mechanical disruption (e.g., milling, cutting, chipping) of cured concrete may release crystalline silica dust. Avoid breathing dust. Wear suitable respiratory protective equipment if processing involves working in areas where dusts are likely to be evolved.

Conditions for safe storage, including any incompatibilities

- Storage temperature Ambient temperatures.
- Incompatible materials Strong oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational Exposure Limits: Applicable only to heated product or milling, cutting, chipping of the product.

| SUBSTANCE. | CAS No. | (8hr TWA) | | (STEL) | | Note: |
|---|---------|---|---------------------------|------------|-------------|-----------|
| | | PEL (OSHA) * | TLV (ACGIH) | PEL (OSHA) | TLV (ACGIH) | |
| Crystalline Silica (respirable particulate) | ----- | $\frac{10 \text{ mg/m}^3}{\% \text{SiO}_2 + 2}$ | 0.025 mg/m ³ ^ | ----- | ----- | See below |

⁽¹⁾ Inhalable benzene-soluble fraction; ^Suspected Human Carcinogen; *Refer to OSHA 29 CFR 1910.1000 & 29 CFR 1926.55; 8hr TWA = 8 hour time-weighted average; STEL = Short Term Exposure Limit.

Recommended monitoring method NIOSH 7500 (Crystalline Silica)

Exposure controls

Appropriate engineering controls Not normally required.

Personal protection equipment

Eye/face protection



The following to be used as necessary: Safety Glasses

Skin protection (Hand protection/ Other)



The following to be used as necessary: Impervious gloves and boots.

Respiratory protection



In case of heating the product or milling, cutting, chipping of the product, respiratory protection may be needed if occupational exposure limits are exceeded. Air-purifying respirator may be sufficient. Check with protective equipment manufacturer's data.



Weldon Materials, Inc.

READY MIX CONCRETE

Reproductive toxicity Not to be expected.

Other information * Mechanical disruption (e.g., milling, cutting, chipping) of cured concrete may release crystalline silica dust.

Crystalline Silica (quartz and cristobalite)

Acute toxicity LD50 (rat): >5000 mg/kg bw
 LD50 (dermal): >2000 mg/kg bw
 LC50 (inhalation, fume): >94.4 mg/m³ - Causes damage to organs: Lungs (silicosis)

Irritation/Corrosivity Not to be expected
 Sensitization Not to be expected
 Repeated dose toxicity Causes damage to organs through prolonged or repeated exposure: Lungs (silicosis)
 Carcinogenicity May cause cancer. Lungs

| NTP | IARC | ACGIH | OSHA |
|-----|------|-------|------|
| No. | Yes. | A2 | Yes. |

Mutagenicity Not to be expected.
Reproductive toxicity Not to be expected.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Short term Not acutely toxic
Long Term Not to be expected.

Persistence and degradability

The product is not biodegradable.

Bioaccumulative potential

The product has no potential for bioaccumulation.

Mobility in soil

The product has low mobility in soil.

Results of PBT and vPvB assessment

Not classified as PBT or vPvB.

Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

Additional Information

None known.

SECTION 14: TRANSPORT INFORMATION

Ground or Water Domestic Voyage (DOT): Not classified as dangerous for transport.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

RCRA Hazardous Waste Number (40 CFR 261.33): None

US RCRA Hazard Class: Not applicable.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

| Chemical Name | CAS No. | Typical %wt. | RQ (Pounds) |
|---------------|---------|--------------|-------------|
| None | ----- | ----- | ----- |

SARA 311/312 - Hazard Categories:

Fire Sudden Release Reactivity Immediate (acute) Chronic (delayed)



Weldon Materials, Inc.

READY MIX CONCRETE

SARA 313 - Toxic Chemicals (40 CFR 372):

| Chemical Name | CAS No. | Typical %wt. |
|---------------|---------|--------------|
| None | ----- | ----- |

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

| Chemical Name | CAS No. | Typical %wt. | TPQ (pounds) |
|---------------|---------|--------------|--------------|
| None | ----- | ----- | ----- |

SECTION 16: OTHER INFORMATION

Additional Information

The following sections contain revisions or new statements: 1-16.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. The manufacturer gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. The manufacturer accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.